

# OpenVPMS ESCI

---

*Integration Guide 1.0-beta-1*



## Contents

1	Overview .....	4
1.1	Contents .....	4
1.2	How it Works .....	4
1.3	Development Environment .....	5
1.4	Supplier Environment .....	6
1.5	Veterinary Practice Environment .....	6
2	Installing the ESCI Package .....	7
2.2	Configuring Tomcat .....	7
2.3	Example web application installation .....	8
2.4	Testing the installation .....	9
3	Using ESCI Examples .....	10
3.1	Submitting orders .....	10
3.2	Checking for responses .....	10
3.3	Retrieving documents from the Inbox .....	10
3.4	Acknowledging receipt of documents in the Inbox .....	11
3.5	Posting Documents to the Inbox .....	11
4	OpenVPMS ESCI Configuration and Testing .....	12
4.1	Configuring OpenVPMS .....	12
4.2	Sending an Order .....	13
4.3	Checking the Inbox .....	15
5	Implementing the API .....	17
5.1	Overview .....	17
5.2	RegistryService .....	17
5.3	OrderService .....	17
5.4	InboxService .....	18
6	UBL Document Structure .....	19
6.1	Order .....	19
6.2	OrderResponseSimple .....	24
6.3	Invoice .....	26
6.4	DocumentReference .....	34
6.5	Document .....	34
7	Code Lists .....	35

7.1	Currency codes .....	35
7.2	Unit of Measure codes .....	35
7.3	Tax Category Identifiers .....	35
7.4	Tax Type Codes .....	35
7.5	Price Type Codes .....	35
7.6	Country codes .....	36
7.7	Country Sub-entity codes.....	36
8	Future Development .....	37

# 1 Overview

OpenVPMS ESCI (e-Supply Chain Interface) is a standards-based API to enable OpenVPMS to place orders and receive order responses and invoices to and from suppliers electronically. It is based on the exchange of Universal Business Language (UBL) 2.0 documents via web services.

## 1.1 Contents

This initial version of ESCI provides the following:

- This Integration document.
- Registry API
- Order placement API
- Inbox API
- Web Service Definition Language (WSDL) and Extensible Markup Language (XML) Schema Definitions (XSD) files, defining the web services
- JAX-WS interfaces, defining the web services in Java
- Java Architecture for XML Binding (JAXB) wrappers for the UBL documents
- Example implementations of the ESCI web services
- Example clients, to submit UBL documents to the ESCI web services
- Example Order, OrderResponseSimple and Invoice UBL documents
- Java classes to submit UBL documents to ESCI web services

## 1.2 How it Works

ESCI defines a number of web services which are implemented by the supplier, namely:

- Order – enables clients to submit orders to the supplier.
- Inbox – enables clients to receive documents posted by the supplier
- Registry - provides a simple lookup mechanism to resolve the other supplier web services. For this release, these are the Order and Inbox services.

OpenVPMS uses the specific supplier's Registry web service to find the URLs of the supplier's Order and Inbox web services

OpenVPMS creates UBL Order documents and submits these to the supplier via the supplier's Order web service.

Orders are processed asynchronously by the supplier.

A UBL OrderResponseSimple document is placed in practice's Inbox, indicating success or failure.

When an order has been shipped, the supplier invoices the practice by placing an UBL Invoice document in its Inbox.

OpenVPMS checks the Inbox web service regularly to process any incoming Order Response and/or Invoice documents.

OpenVPMS notifies the users of incoming documents using messages.

OpenVPMS also processes these documents by either updating order status or by generating new deliveries.

The Practice actions the messages and processes the delivery information as per their internal procedures.

### 1.3 Development Environment

ESCI is based around common open standards and the API's can be implemented on any platform or development environment that supports development of Web services as per WS-I Basic Profile 1.1 (<http://www.ws-i.org/Profiles/BasicProfile-1.1.html>)

The ESCI example implementation and clients are written in Java and will operate on any platform that supports:

- Java 1.6.x or higher

See <http://www.oracle.com/technetwork/java/javase/downloads/index.html>

- Apache Tomcat

At the time of writing, Apache Tomcat 7 was available, although Apache Tomcat 5.5 and higher should be compatible.

See <http://tomcat.apache.org/download-70.cgi>

To install a complete test environment suitable for integration testing with OpenVPMS you will need:

- OpenVPMS 1.5

This is available from <http://repository.openvpms.org/releases/org/openvpms/openvpms-release/1.5-beta-1/openvpms-release-1.5-beta-1.zip>

With the exception of the Java version above, the installation requirements are the same as those documented at <http://www.openvpms.org/openvpms-installation-windows>

Installation for other platforms is documented at:

<http://www.openvpms.org/implementors-handbook>

- Test Database

The OpenVPMS 1.5 release includes a demo database that can be used for this purpose. To load this database first make sure you have run the **dataload setup** command as outlined in the **OpenVPMS Database Setup** section of the Installation notes referenced above.

Then run the following command to load the demo data:

```
dataload.bat -d ../import/data/demo -s
```

## 1.4 Supplier Environment

In order to do full integration testing and production setup with OpenVPMS the supplier needs to have developed and deployed the web services as described in this document.

The supplier will also need to setup suitable authentication and account details for the veterinary practice.

Suppliers may choose to implement ESCI as secure web services accessible over the internet. Alternatively, they may choose to deploy an application in the practice which provides these services to OpenVPMS – this application would then utilise their pre-existing communication protocol.

## 1.5 Veterinary Practice Environment

In order for the Veterinary Practice to utilise ESCI services they will need:

- OpenVPMS 1.5
- Internet access (dependent on the supplier mode of deployment)
- Details of supplier ESCI service URL's, authentication and Account details.
- Optional: Supplier installed and configured middleware application.
- OpenVPMS Supplier configuration as per the notes included in this document.

## 2 Installing the ESCI Package

The ESCI package is contained in a zip named:

```
openvpms-es-ci-package-<version>.zip
```

In the above, **<version>** indicates the release version.

Extract this using your favourite zip program, or the Java jar tool:

```
jar xvf openvpms-es-ci-package-<version>.zip
```

This will extract to a directory named `openvpms-es-ci-package-<version>`.

For the rest of this document:

- **<ESCI\_HOME>** Refers to the base directory where the ESCI package was installed. This must be replaced with the actual directory path on the command line, and in configuration files.
- **<TOMCAT\_HOME>** Refers to Tomcat's base directory. This must be replaced with the actual directory path on the command line, and in configuration files.
- **JAVA\_HOME** Refers to the environment variable pointing to the base directory of the java installation. This is configured as part of the OpenVPMS installation

In shells and configuration files, they need to be replaced with their actual values.

### Directory Structure

The package has the following sub-directories:

doc/	ESCI documentation
bin/	contains scripts for running the client examples
conf/	contains configuration files for the examples
data/	contains sample UBL documents
lib/	contains jars used by the examples in bin/
src/	contains the source code for the examples
webapp/	contains the example web application
wSDL/	contains the WSDL and XSD files defining the ESCI web services

## 2.2 Configuring Tomcat

### SSL Configuration

Tomcat needs to be configured to use SSL (Secure Socket Layer). This is a technology which allows web browsers and web servers to communicate over a secured connection. To simplify things, the examples come with a self-signed certificate "tomcat", contained in the keystore:

```
<ESCI_HOME>/conf/tomcat.jks.
```

This certificate only works on “localhost”.

Edit `<CATALINA_HOME>/conf/server.xml` and uncomment and change the SSL connector:

```
<!-- Define a SSL Coyote HTTP/1.1 Connector on port 8443 -->
<Connector port="8443" protocol="HTTP/1.1" SSLEnabled="true"
    maxThreads="150" scheme="https" secure="true"
    keystoreFile="<ESCI_HOME>/conf/tomcat.jks"
    keystorePass="changeit"
    clientAuth="false" sslProtocol="TLS" />
```

The certificate also needs to be imported into the Java runtime’s `cacerts` file. Take a backup of the file first, so it can be restored after testing is complete.

Windows<sup>1</sup>:

```
keytool -exportcert -alias tomcat -keystore tomcat.jks -storepass changeit -file tomcat.cert
keytool -importcert -alias tomcat -keystore %JAVA_HOME%\jre\lib\security\cacerts \
    -storepass changeit -file tomcat.cert
```

Enter “yes” when prompted, i.e.:

```
Trust this certificate? [no]: yes
```

A longer discussion on SSL and key stores can be found at <http://tomcat.apache.org/tomcat-7.0-doc/ssl-howto.html>

### User Configuration

For these examples, a user needs to be added to Tomcat's user database.

The default tomcat installation stores user information in:

```
<TOMCAT_HOME>/conf/tomcat-users.xml
```

Add the following entries:

```
<role rolename="ESCI"/>
<user username="esci" password="example" roles="ESCI"/>
```

See <http://tomcat.apache.org/tomcat-7.0-doc/realms-howto.html#UserDatabaseRealm> for more details.

## 2.3 Example web application installation

To install the example web application, copy:

```
<ESCI_HOME>/webapp/esci-example.war
```

To the directory:

---

<sup>1</sup> Ignore the trailing \ character. This is to indicate that the command needs to be entered on a single line

`<TOMCAT_HOME>/webapps`

## 2.4 Testing the installation

To test the installation, start Tomcat so that it logs to the current console window:

Windows:

```
cd <TOMCAT_HOME>\bin
catalina.bat run
```

Unix:

```
cd <TOMCAT_HOME>/bin
catalina.sh run
```

Now open up a web browser and enter the URL<sup>2</sup>:

`https://localhost:8443/esci-example/RegistryService?wsdl`

A dialog should pop up, requesting a user name and password. Enter 'esci' and 'example' respectively (without quotes).

The WSDL for the RegistryService should be displayed.

---

<sup>2</sup> NOTE: Your browser will warn you that the connection is untrusted as the security certificate wasn't issued by a trusted certificate authority. For the purposes of testing, this can be ignored. In a production environment, the certificate needs to be issued by a trusted authority, to simplify deployment

## 3 Using ESCI Examples

### 3.1 Submitting orders

To submit an order:

```
cd <ESCI_HOME>/bin
order.bat -f ../data/order1.xml -u esci -p example
```

The example OrderService will:

- log the order to the console
- create a response
- create an invoice for the order

This connects to the default registry URL. To override this, specify `-r` on the command line, e.g.:

```
order.bat -f ../data/order1.xml -u esci -p example \
-r https://localhost:8443/esci-example/RegistryService?wsdl
```

### 3.2 Checking for responses

Both order responses and invoices are placed in the inbox of the practice placing the order.

To check responses:

```
cd <ESCI_HOME>/bin
inbox.bat -l -u esci -p example
```

This will list available documents, e.g.:

```
Available documents: 2

<cac:DocumentReference
  xmlns="urn:oasis:names:specification:ubl:schema:xsd:CommonBasicComponents-2"
  xmlns:cac="urn:oasis:names:specification:ubl:schema:xsd:CommonAggregateComponents-2">
  <ID>21</ID>
  <DocumentType>OrderResponseSimple</DocumentType>
</cac:DocumentReference>

<cac:DocumentReference
  xmlns="urn:oasis:names:specification:ubl:schema:xsd:CommonBasicComponents-2"
  xmlns:cac="urn:oasis:names:specification:ubl:schema:xsd:CommonAggregateComponents-2">
  <ID>22</ID>
  <DocumentType>Invoice</DocumentType>
</cac:DocumentReference>
```

### 3.3 Retrieving documents from the Inbox

Documents can be retrieved by specifying their identifier and type, e.g.:

```
cd <ESCI_HOME>/bin
inbox.bat -g -i 21 -t OrderResponseSimple -u esci -p example
```

If available, the corresponding document will be displayed.

### 3.4 Acknowledging receipt of documents in the Inbox

Documents will continue to be returned by the InboxService until acknowledged. To acknowledge a document:

```
cd <ESCI_HOME>/bin
inbox.bat -g -i 21 -t OrderResponseSimple -u esci -p example
```

### 3.5 Posting Documents to the Inbox

Documents can be posted to the Inbox as follows:

```
cd <ESCI_HOME>/bin
post.bat -f ../data/responses1.xml -u esci -p example
```

Note that this service is not part of the ESCI API, and exists solely for testing purposes.

## 4 OpenVPMS ESCI Configuration and Testing

The following describes how to setup OpenVPMS to use ESCI.

For testing purposes the sample web services will be used to receive orders and generate order responses and invoices.

The sample services provide limited validation of documents – they simply check that documents conform to their relevant UBL schema.

It will be necessary for suppliers to perform full integration testing between OpenVPMS and their ESCI service implementations in order to completely validate the operation of their services.

### 4.1 Configuring OpenVPMS

In order for OpenVPMS to send orders to the sample OrderService, it must first be configured. Login to the web application at <http://localhost:8080/openvpms/login> as user “admin”, password “admin” and:

- Configure a supplier for ESCI

A number of suppliers are included in the sample data. Go to the **Suppliers→Information** workspace, select one, and edit it. Alternatively, a new supplier can be created via the **New** button.

- In the “Stock Locations” tab, click **Add** to add a new “Supplier Stock Location Relationship for e-Supply Chain Interfacing”
- Select “Main Stock Clinic” for the Stock Location
- Enter an Account ID.
- Enter “<https://localhost:8443/esci-example/RegistryService?wsdl>” for the Service URL
- Enter “esci” for Username
- Enter “example” for Password
- Click **Test to** verify the details. A message “Successfully connected to supplier” should be displayed.
- Click **OK** to finish editing the supplier

**New Supplier(Organisation)**

Id: -1

Company Name: Acme Veterinary Wholesaler

Active:

1 Contacts | 2 Representatives | 3 Account Type | 4 Categories | 5 Stock Locations

Add | Delete | Previous | Next |  Hide Inactive Stock Locations

Name	Description	Details
New Supplier Stock Location Relationship for e-Supply Chain Interfacing		
Stock Location	Green Vale Stock	Username: esci
Account ID	123456A	Password: example
Service URL	https://localhost:8443/esci-example/RegistryService?wsdl	Test

Apply | OK | Cancel

#### Notes:

1. The Account ID is used to populate the SupplierAssignedAccountID in the Order document. Although not necessary for the example services, this may be required by the receiving supplier in a production environment.
2. OpenVPMS supports multiple stock locations. Each stock location may be associated with multiple suppliers. The supplier/stock location relationship determines which service URL and authentication details to use to connect to the supplier. These details must correspond to a unique Inbox; i.e. documents posted to the Inbox must be for the supplier/stock location only.
3. In the case where a supplier requires different account identifiers based on the products being ordered, e.g. Medication vs. Food, a separate supplier must be created.

## 4.2 Sending an Order

- Create an order

Ordering is done in the **Suppliers → Orders** workspace. Click **New** to create a new order.

- In the “New Order” dialog select the supplier edited above.
- Select “Main Stock Clinic” for Stock Location
- Click **OK** to launch the order editor
- Edit the order
  - Click **Add** on the “Items” tab to add a new order item
  - Select a product for Product, e.g. “Amoxil 250mg Capsules”
  - Enter a Reorder Code e.g. “123456”
  - Enter a package size e.g. 500
  - Enter a package units e.g. Bottle

- Enter a Quantity e.g. 2
- Enter a Nett Price e.g. 133.50
- Enter a List Price e.g. 133.50
- Click **OK** to save the order and finish editing

**New Order**
✕

Supplier	Acme Veterinary Wholesaler	Tax	\$0.00
Stock Location	Green Vale Stock	Printed	<input type="checkbox"/>
Date	23/01/2011	Status	In Progress
Notes			
Amount	\$293.70	Delivery Status	Pending
		Supplier Response	

Items

Add
Delete
Previous
Next

Product	Reorder Code	Reorder Description	Package Size	Package Units	Quantity	Received Quantity	Cancelled Quantity	Nett Price	List Price	Tax	Total
New Order Item											
Product	Amoxil 250mg Capsule				Received Quantity	0.00					
Reorder Code	123456				Cancelled Quantity	0.00					
Reorder Description	Bottle of Amoxil 250mg Capsules				Nett Price	133.50					
Package Size	500				List Price	133.50					
Package Units	Bottle				Tax	\$26.70					
Quantity	2.00				Total	\$293.70					

Apply
OK
Cancel

- Finalise the order
  - In the supplier orders table, select the order and click **Finalise**
  - Click **OK** on the “Are you sure you want to Finalise the Order?” prompt

**Supplier - Orders**

Supplier [Acme Veterinary Whole](#) Stock Location  Status **In Progress** Delivery Status **Pending**

All From  To

Date	Supplier	Stock Location	Status	Delivery Status	Amount	Notes
23/01/2011	Acme Veterinary Wholesaler	Green Vale Stock	In Progress	Pending	\$293.70	

---

Supplier [Acme Veterinary Wholesaler](#) Tax   
 Stock Location [Green Vale Stock](#) Printed   
 Date  Status   
 Notes   
 Amount  Delivery Status   
 Supplier Response

Items

Product	Reorder Code	Reorder Description	Package Size	Package Units	Quantity	Received Quantity	Cancelled Quantity	Nett Price	List Price	Tax	Total
<a href="#">Amoxicil 250mg Capsules</a>	123456	Bottle of Amoxicil 250mg Capsules	500	Bottle	2.00	0.00	0.00	\$133.50	\$133.50	\$26.70	\$293.70

### 4.3 Checking the Inbox

On receiving the Order the ESCI example services will do two things:

- Display the original order document on the Tomcat console.
- Queue an UBL **OrderResponseSimple** and an **Invoice** document in the Example ESCI Inbox service ready to be picked up by OpenVPMS when it next checks this service.

OpenVPMS periodically checks each configured Inbox. By default this is scheduled to occur once daily.

You can also manually check for documents in the **Suppliers → Orders** and **Supplier → Deliveries** Workspaces by clicking on the **Check Inbox** button.

On clicking this button you should note that the Messages icon in the menu bar indicates new messages. Clicking this icon will take you to the **Workflow → Messages** workspace where you should see two (2) unread messages.

**Workflow - Messaging**

Type: **All** Status: **Pending**  All From: **Jan 23, 2011** To: **Jan 23, 2011** **Find**

User: **admin**

To	Start Time	Reason	Description	Status	Item
admin	23/01/2011	Order accepted		Pending	Order
admin	23/01/2011	Order invoiced		Pending	Delivery

---

To: **admin** Description:

Start Time: **23/01/2011** Status: **Pending**

Reason: **Order accepted**

Item:

Supplier: **Acme Veterinary Wholesaler** Tax: **\$13.35**

Stock Location: **Green Vale Stock** Printed:

Date: **23/01/2011** Status: **Accepted**

Notes:  Delivery Status: **Pending**

Amount: **\$146.85** Supplier Response: **Order accepted**

Items:

Product	Reorder Code	Reorder Description	Package Size	Package Units	Quantity	Received Quantity	Cancelled Quantity	Nett Price	List Price	Tax	Total
Amoxil 250mg Capsules	123456	Bottle of Amoxil 250mg Capsules	500	Bottle	1.00	0.00	0.00	\$133.50	\$133.50	\$13.35	\$146.85

**New Forward Completed Print**

One message relates to the received **OrderResponseSimple** document, and should have a reason of **Order Accepted**. The message displays the order that the response relates to, indicating that it now has a status of **Accepted**. The updated order can also be seen in the **Suppliers→Orders** workspace.

The second message relates to the received **Invoice** document, and should have a reason of **Order Invoiced**. OpenVPMS generates deliveries for Invoice documents - the message displays this delivery, with a status of **In Progress**. This can also be seen in the **Suppliers→Deliveries** workspace

OpenVPMS does not finalise the delivery automatically. This allows the delivery information to be reviewed and modified by the practice staff should there be any discrepancies with the physical delivery received by the practice.

On Finalising the Delivery, OpenVPMS will update stock quantities and purchase prices and perform any selling price updates required. The latter is determined by whether list prices have changed and if the specific Product Supplier information stipulates Auto price updates.

## 5 Implementing the API

### 5.1 Overview

In order to implement ESCI, the following web services must be developed:

- RegistryService
- OrderService
- InboxService

For Java, an interface for each service is provided. The java API documentation for these interfaces is located in:

`<ESCI_HOME>/doc/api/index.html`

For other platforms, code for the services can be generated from the WSDL files provided in the **wSDL/** directory of the examples package.

For .NET, this can be done using the svcutil tool. See <http://msdn.microsoft.com/en-us/library/aa751905.aspx> for more details.

In Visual Studio, this can be done by adding a reference to the web service as per: <http://msdn.microsoft.com/en-us/library/bb628649.aspx>.

### 5.2 RegistryService

The RegistryService provides a simple means to locate the other web services.

Method	Description
<b>getInboxService</b>	Returns the InboxService WSDL URL.
<i>Parameters</i>	None
<i>Returns</i>	String The InboxService WSDL URL
<b>getOrderService</b>	Returns the OrderService WSDL URL.
<i>Parameters</i>	None
<i>Returns</i>	String The OrderService WSDL URL

### 5.3 OrderService

The OrderService enables the authenticated user to place orders with the supplier.

Method	Description
<b>submitOrder</b>	Submits an order to the supplier.

	<p>If the order is accepted, an <b>OrderResponseSimple</b> document will be placed in the customer's corresponding Inbox, with <b>AcceptedIndicator=true</b>.</p> <p>If the order is rejected, the <b>OrderResponseSimple</b> document have <b>AcceptedIndicator=false</b> and the reason for rejection described in the <b>RejectionNote</b>.</p> <p>If the submit fails for any reason other than <b>DuplicateOrderException</b>, the client may resubmit the Order.</p>	
<i>Parameters</i>	order: <a href="#">Order</a>	The order to submit
<i>Returns</i>	None	
<i>Throws</i>	DuplicateOrderException	If the order has an identifier the same as another submitted previously

## 5.4 InboxService

The InboxService enables authenticated users to access documents placed in their Inbox by the supplier.

The supplier places [OrderResponseSimple](#) documents in a user's Inbox on receipt of an [Order](#).

If an order is accepted, the supplier will place an [Invoice](#) document in the Inbox. This may happen immediately, or at some later stage, according to the supplier's business rules.

Method	Description	
<b>getDocuments</b>	<p>Returns a list of references to documents in the Inbox.</p> <p>Each reference must refer to a unique document.</p> <p>The references must be in the same order that the documents were added, with the oldest document referenced first.</p> <p>For this release, only <a href="#">Invoice</a> and <a href="#">OrderResponseSimple</a> documents may be referenced.</p>	
<i>Parameters</i>	None	
<i>Returns</i>	List of <a href="#">DocumentReference</a>	
<b>getDocument</b>	Returns a document, given its reference.	
<i>Parameters</i>	reference: <a href="#">DocumentReference</a>	The document reference
<i>Returns</i>	<a href="#">Document</a>	The corresponding document, or null if none is found. For this release, only documents containing <a href="#">Invoice</a> or <a href="#">OrderResponseSimple</a> may be returned.
<b>acknowledge</b>	Acknowledges a document.	
	This removes the document from the Inbox. It will no longer be returned by <b>getDocument()</b> nor <b>getDocuments()</b> .	
<i>Parameters</i>	reference: <a href="#">DocumentReference</a>	The document reference
<i>Returns</i>	None	
<i>Throws</i>	DocumentNotFoundException	If the reference doesn't refer to a valid document

## 6 UBL Document Structure

OpenVPMS uses a subset of the UBL 2.0 specification. For this release, it uses the following documents:

- Order
- OrderResponseSimple
- Invoice

It also uses the UBL DocumentReference type, when referring to documents in an Inbox.

The usage of these will be specified in the following sections. Please read the notes associated with each as they provide further information on how OpenVPMS supplies and processes some of the key information in these documents.

### 6.1 Order

Element	Type	Use	Description
UBLVersionID	IdentifierType	1	UBL version identifier. Must be <b>2.0</b>
ID	IdentifierType	1	The buyer assigned order identifier
IssueDate	DateType	1	The date the buyer issued the order
IssueTime	TimeType	0..1	The time the buyer issued the order
BuyerCustomerParty	CustomerPartyType	1	Buyer details
SellerSupplierParty	SupplierPartyType	1	Seller details
AnticipatedMonetaryTotal	MonetaryTotalType	1	The anticipated total amounts
OrderLine	OrderLineType	1..*	The order items

#### Example

```
<Order xmlns:cbc="urn:oasis:names:specification:ubl:schema:xsd:CommonBasicComponents-2"
      xmlns:cac="urn:oasis:names:specification:ubl:schema:xsd:CommonAggregateComponents-2"
      xmlns="urn:oasis:names:specification:ubl:schema:xsd:Order-2">
  <cbc:UBLVersionID>2.0</cbc:UBLVersionID>
  <cbc:ID>276</cbc:ID>
  <cbc:IssueDate>2010-03-21</cbc:IssueDate>
  + <cac:BuyerCustomerParty/>
  + <cac:SellerSupplierParty/>
  + <cac:AnticipatedMonetaryTotal/>
  + <cac:OrderLine/>
  + <cac:OrderLine/>
</Order>
```

#### Order.BuyerCustomerParty

Name	Type	Use	Description
CustomerAssignedAccountID	Identifier	1	The buyer assigned identifier for the customer
SupplierAssignedAccountID	Identifier	0..1	The seller assigned identifier for the customer
Party	PartyType	1	Buyer details

### Example

```
<cac:BuyerCustomerParty>
  <cbc:CustomerAssignedAccountID>58</cbc:CustomerAssignedAccountID>
  <cbc:SupplierAssignedAccountID>123899123</cbc:SupplierAssignedAccountID>
  + <cac:Party/>
</cac:BuyerCustomerParty>
```

### Notes

1. OpenVPMS sets the **SupplierAssignedAccountID** to the **Account ID** field setup in the Supplier Stock Location relationship as detailed in section 4.1, if present.
2. The **CustomerAssignedAccountID** is set to the internal unique ID for the Stock Location.

## Order.BuyerCustomerParty.Party

Name	Type	Use	Description
PartyName	PartyNameType	1	Buyer name
PostalAddress	AddressType	1	Buyer postal address
Contact	ContactType	1	Buyer contact

### Example

```
<cac:Party/>
  + <cac:PartyName/>
  + <cac:PostalAddress/>
  + <cac:Contact/>
</cac:Party>
```

## Order.BuyerCustomerParty.Party.PartyName

Name	Type	Use	Description
Name	NameType	1	Buyer name

### Example

```
<cac:PartyName>
  <cbc:Name>OpenVPMS Demonstration Practice</cbc:Name>
</cac:PartyName>
```

## Order.BuyerCustomerParty.Party.PostalAddress

Name	Type	Use	Description
CityName	NameType	1	City or town name
PostalZone	TextType	1	Post code
CountrySubentity	TextType	1	State
AddressLine	AddressLineType	1	Formatted address line

### Example

```
<cac:PostalAddress>
  <CityName>Cape Woolamai</CityName>
  <cbc:PostalZone>3925</cbc:PostalZone>
  <cbc:CountrySubentity>Victoria</cbc:CountrySubentity>
  + <cac:AddressLine/>
</cac:PostalAddress>
```

## Order.BuyerCustomerParty.Party.PostalAddress.AddressLine

Name	Type	Use	Description
Line	TextType	1	Formatted address line

### Example

```
<cac:AddressLine>
  <cbc:Line>1 Broadwater Avenue</cbc:Line>
</cac:AddressLine>
```

## Order.BuyerCustomerParty.Party.Contact

Name	Type	Use	Description
Name	NameType	0..1	Buyer contact name
Telephone	TextType	0..1	Buyer telephone
Telefax	TextType	0..1	Buyer fax
ElectronicMail	TextType	0..1	Buyer email

### Example

```
<cac:Contact>
  <cbc:Name>Joe Bloggs</cbc:Name>
  <cbc:Telephone>59527054</cbc:Telephone>
  <cbc:Telefax>59527053</cbc:Telefax>
  <cbc:ElectronicMail>foo@bar.com</cbc:ElectronicMail>
</cac:Contact>
```

## Order.SellerSupplierParty

Name	Type	Use	Description
CustomerAssignedAccountID	IdentifierType	1	The buyer assigned identifier for the supplier
Party	PartyType	1	Seller details

### Example

```
<cac:SellerSupplierParty>
  <cbc:CustomerAssignedAccountID>948</cbc:CustomerAssignedAccountID>
  + <cac:Party/>
</cac:SellerSupplierParty>
```

### Notes

1. OpenVPMS sets the **CustomerAssignedAccountID** to the internal unique ID for the Supplier.

## Order.SellerSupplierParty.Party

Name	Type	Use	Description
PartyName	PartyNameType	1	Seller name
PostalAddress	AddressType	0..1	Seller postal address

### Example

```
<cac:Party/>
  + <cac:PartyName/>
  + <cac:PostalAddress/>
</cac:Party>
```

## Order.SellerSupplierParty.Party.PartyName

Name	Type	Use	Description
Name	NameType	1	Seller name

### Example

```
<cac:PartyName>
  <cbc:Name>Vet Supplies</cbc:Name>
</cac:PartyName>
```

## Order.SellerSupplierParty.Party.PostalAddress

Name	Type	Use	Description
CityName	NameType	1	City or town name
PostalZone	TextType	1	Post code
CountrySubentity	TextType	1	State
AddressLine	AddressLineType	1	Formatted address line

### Example

```
<cac:PostalAddress>
  <cbc:CityName>Tennant Creek</cbc:CityName>
  <cbc:PostalZone>0862</cbc:PostalZone>
  <cbc:CountrySubentity>Northern Territory</cbc:CountrySubentity>
  + <cac:AddressLine/>
</cac:PostalAddress>
```

## Order.SellerSupplierParty.Party.PostalAddress.AddressLine

Name	Type	Use	Description
Line	TextType	1	Formatted address line

### Example

```
<cac:AddressLine>
  <cbc:Line>2 Peko Rd</cbc:Line>
</cac:AddressLine>
```

## Order.AnticipatedMonetaryTotal

Name	Type	Use	Description
PayableAmount	Amount	1	The anticipated payable amount
PayableAmount@currencyID	CurrencyCodeContentType	1	The <a href="#">currency code</a>

### Example

```
<cac:AnticipatedMonetaryTotal>
  <cbc:PayableAmount currencyID="AUD">55.00</cbc:PayableAmount>
</cac:AnticipatedMonetaryTotal>
```

## Order.OrderLine

Name	Type	Use	Description
LineItem	LineItemType	1..*	Order line item

### Example

```
<cac:OrderLine>
  + <cac:LineItem>
</cac:OrderLine>
```

## Order.OrderLine.LineItem

Name	Type	Use	Description
ID	IdentifierType	1	The order line identifier, assigned by the buyer

Quantity	QuantityType	1	The quantity
Quantity@unitCode	String	1	The <a href="#">unit of measure code</a> for the quantity.
LineExtensionAmount	AmountType	1	The line total, excluding taxes
LineExtensionAmount@currencyID	CurrencyCodeContentType	1	The <a href="#">currency code</a> the LineExtensionAmount is expressed in
TotalTaxAmount	AmountType	1	The anticipated tax amount
TotalTaxAmount@currencyID	CurrencyCodeContentType	1	The <a href="#">currency code</a> the TotalTaxAmount is expressed in
Price	PriceType	1	The item price
Item	ItemType	1	The item

### Example

```
<cac:LineItem>
  <cbc:ID>277</cbc:ID>
  <cbc:Quantity unitCode="BX">1.000</cbc:Quantity>
  <cbc:LineExtensionAmount currencyID="AUD">55.00</cbc:LineExtensionAmount>
  <cbc:TotalTaxAmount currencyID="AUD">5.50</cbc:TotalTaxAmount>
  + <cac:Price/>
  + <cac:Item/>
</cac:LineItem>
```

### Order.OrderLine.LineItem.Price

Name	Type	Use	Description
PriceAmount	AmountType	1	The price
PriceAmount@currencyID	CurrencyCodeContentType	1	The <a href="#">currency code</a> that PriceAmount is expressed in
BaseQuantity	QuantityType	1	The base quantity for the price.
BaseQuantity@unitCode		1	The <a href="#">unit of measure code</a> for the base quantity.

### Example

```
<cac:Price>
  <cbc:PriceAmount currencyID="AUD">55.000</cbc:PriceAmount>
  <cbc:BaseQuantity unitCode="BX">1</cbc:BaseQuantity>
</cac:Price>
```

### Notes

1. BaseQuantity is limited to 1 for this release of ESCI.

### Order.OrderLine.LineItem.Item

Name	Type	Use	Description
Description	TextType	0..1	The item description
Name	TextType	1	The item name
BuyersItemIdentification	ItemIdentificationType	1	The buyer assigned item identifier
SellersItemIdentification	ItemIdentificationType	1	The seller assigned item identifier

### Example

```
<cac:Item>
  <cbc:Description>Advantage Dog Large 10-25Kg Maroon</cbc:Description>
  <cbc:Name>Advantage Dog Large</cbc:Name>
  + <cac:BuyersItemIdentification/>
  + <cac:SellersItemIdentification/>
</cac:Item>
```

### Order.OrderLine.LineItem.Item.BuyersItemIdentification

Name	Type	Use	Description
ID	IdentifierType	1	The buyer assigned item identifier

### Example

```
<cac:BuyersItemIdentification>
  <cbc:ID>945</cbc:ID>
</cac:BuyersItemIdentification>
```

### Notes

1. OpenVPMS sets the **BuyersItemIdentification** to the internal unique ID for the Product being ordered.

### Order.OrderLine.LineItem.Item.SellersItemIdentification

Name	Type	Use	Description
ID	IdentifierType	1	The seller assigned item identifier

### Example

```
<cac:SellersItemIdentification>
  <cbc:ID>ADVAND623</cbc:ID>
</cac:SellersItemIdentification>
```

### Notes

1. OpenVPMS sets the **SellersItemIdentification** to the **Reorder Code** entered in the order line.
2. OpenVPMS stores the Reorder Code for each supplier in Product Supplier relationship information which can be found in the **Product → Information** workspace on the **Supplier** tab.

## 6.2 OrderResponseSimple

Element	Type	Use	Description
UBLVersionID	IdentifierType	1	UBL version identifier. Must be <b>2.0</b>
ID	IdentifierType	1	The seller assigned response identifier
IssueDate	DateType	1	The date when the response was issued
Note	TextType	0..*	Free form text
AcceptedIndicator	IndicatorType	1	Indicates if the order was accepted (true) or not (false)
RejectionNote	TextType	0..1	The reason for rejection if the order was not accepted
OrderReference	OrderReferenceType	1	The order that the response refers to
SellerSupplierParty	SupplierPartyType	1	The seller details
BuyerCustomerParty	CustomerPartyType	1	The buyer details

## Example

```
<?xml version="1.0" encoding="UTF-8"?>
<OrderResponseSimple
  xmlns="urn:oasis:names:specification:ubl:schema:xsd:OrderResponseSimple-2"
  xmlns:cac="urn:oasis:names:specification:ubl:schema:xsd:CommonAggregateComponents-2"
  xmlns:cbc="urn:oasis:names:specification:ubl:schema:xsd:CommonBasicComponents-2">
  <cbc:UBLVersionID>2.0</cbc:UBLVersionID>
  <cbc:ID>66890-9-09</cbc:ID>
  <cbc:IssueDate>2005-06-20</cbc:IssueDate>
  <cbc:Note>sample</cbc:Note>
  <cbc:AcceptedIndicator>true</cbc:AcceptedIndicator>
  + <cac:OrderReference/>
  + <cac:SellerSupplierParty/>
  + <cac:BuyerCustomerParty/>
</OrderResponseSimple>
```

## Notes

1. The ID must be unique for all OrderResponseSimple documents for a given buyer. The Order identifier cannot be used for this purpose as ESCI will support order amendment in a future version of ESCI – a new OrderResponseSimple must be generated with another identifier in this case.

## OrderResponseSimple.OrderReference

Element	Type	Use	Description
ID	IdentifierType	1	The order identifier

## Example

```
<cac:OrderReference>
  <cbc:ID>726</cbc:ID>
</cac:OrderReference>
```

## OrderResponseSimple.SellerSupplierParty

Element	Type	Use	Description
CustomerAssignedAccountID	IdentifierType	0..1	The buyer assigned identifier for the seller
AdditionalAccountID	IdentifierType	0..1	The seller assigned identifier for the seller

## Example

```
<cac:SellerSupplierParty>
  <cbc:CustomerAssignedAccountID>1234</cbc:CustomerAssignedAccountID>
</cac:SellerSupplierParty>
```

## Notes

1. OpenVPMS requires that one or both of **CustomerAssignedAccountID** or **AdditionalAccountID** be provided.
2. If **CustomerAssignedAccountID** is used, it must correspond to that sent in the original order. This is the preferred identifier.
3. If **AdditionalAccountID** is used, it must match the **Account ID** field setup in the Supplier Stock Location relationship, as detailed in section 4.1.

## OrderResponseSimple.BuyerCustomerParty

Element	Type	Use	Description
CustomerAssignedAccountID	IdentifierType	0..1	The buyer assigned identifier for the buyer
SupplierAssignedAccountID	IdentifierType	0..1	The seller assigned identifier for the buyer

### Example

```
<cac:BuyerCustomerParty>
  <cbc:CustomerAssignedAccountID>1234</cbc:CustomerAssignedAccountID>
</cac:BuyerCustomerParty>
```

### Notes

1. OpenVPMS requires that one or both of **CustomerAssignedAccountID** or **SupplierAssignedAccountID** be provided.
2. If **CustomerAssignedAccountID** is used, it must correspond to that sent in the original order. This is the preferred identifier.
3. If **SupplierAssignedAccountID** is used, it must match the **Account ID** field setup in the Supplier Stock Location relationship, as detailed in section 4.1.

## 6.3 Invoice

Element	Type	Use	Description
UBLVersionID	IdentifierType	1	UBL version identifier. Must be <b>2.0</b>
ID	IdentifierType	1	The invoice identifier, assigned by the supplier
IssueDate	DateType	1	The date the invoice was issued
IssueTime	TimeType	0..1	The time the invoice was issued
Note	TextType	0..*	Supplier provided note
OrderReference	OrderReferenceType	0..1	Reference to the original order
AccountSupplierParty	SupplierPartyType	1	The supplier information
AccountingCustomerParty	CustomerPartyType	1	The customer information
AllowanceCharge	AllowanceChargeType	0..*	Any allowances or charges associated with the invoice. For this release, only charges (e.g. freight) are supported.
TaxTotal	TaxTotalType	0..1	The total tax on the invoice
LegalMonetaryTotal	MonetaryTotalType	1	Total amounts
InvoiceLine	InvoiceLineType	1..*	Invoice items

### Example

```
<?xml version="1.0" encoding="UTF-8" standalone="yes"?>
<Invoice xmlns:cbc="urn:oasis:names:specification:ubl:schema:xsd:CommonBasicComponents-2"
  xmlns:cac="urn:oasis:names:specification:ubl:schema:xsd:CommonAggregateComponents-2"
  xmlns="urn:oasis:names:specification:ubl:schema:xsd:Invoice-2">
  <cbc:UBLVersionID>2.0</cbc:UBLVersionID>
  <cbc:ID>12345</cbc:ID>
  <cbc:IssueDate>2010-11-01</cbc:IssueDate>
  <cbc:IssueTime>17:12:08.265</cbc:IssueTime>
  <cbc:Note>a note</cbc:Note>
  <cbc:Note>another note</cbc:Note>
  + <cac:OrderReference/>
  + <cac:AccountingSupplierParty/>
  + <cac:AccountingCustomerParty/>
  + <cac:AllowanceCharge/>
  + <cac:TaxTotal/>
  + <cac:LegalMonetaryTotal/>
  + <cac:InvoiceLine/>
  + <cac:InvoiceLine/>
</Invoice>
```

### Invoice.OrderReference

Element	Type	Use	Description
---------	------	-----	-------------

ID	IdentifierType	1	Order identifier, from the original order
----	----------------	---	---

#### Example

```
<cac:OrderReference>
  <cbc:ID>20122</cbc:ID>
</cac:OrderReference>
```

#### Notes

1. When specified, all InvoiceLine elements that reference an order line using the OrderLineReference element must refer to this order.
2. When an Invoice refers to multiple orders, this element should not be specified. Each InvoiceLine must fully specify the associated order.

### Invoice.AccountingSupplierParty

Element	Type	Use	Description
CustomerAssignedAccountID	IdentifierType	0..1	The customer assigned identifier for the supplier
AdditionalAccountID	IdentifierType	0..1	The supplier assigned identifier for the supplier

#### Example

```
<cac:AccountingSupplierParty>
  <cbc:CustomerAssignedAccountID>12089</cbc:CustomerAssignedAccountID>
</cac:AccountingSupplierParty>
```

#### Notes

1. OpenVPMS requires that one or both of **CustomerAssignedAccountID** or **AdditionalAccountID** be provided.
2. If **CustomerAssignedAccountID** is used, it must correspond to that sent in the original order. This is the preferred identifier.
3. If **AdditionalAccountID** is used it must match the **Account ID** field setup in the Supplier Stock Location relationship, as detailed in section 4.1.

### Invoice.AccountingCustomerParty

Element	Type	Use	Description
CustomerAssignedAccountID	IdentifierType	0..1	The customer assigned identifier for the customer
SupplierAssignedAccountID	IdentifierType	0..1	The supplier assigned identifier for the customer

#### Example

```
<cac:AccountingCustomerParty>
  <cbc:CustomerAssignedAccountID>12087</cbc:CustomerAssignedAccountID>
</cac:AccountingCustomerParty>
```

#### Notes

1. OpenVPMS requires that one or both of **CustomerAssignedAccountID** or **SupplierAssignedAccountID** be provided.
2. If **CustomerAssignedAccountID** is used, it must correspond to that sent in the original order. This is the preferred identifier.
3. If **SupplierAssignedAccountID** is used it must match the **Account ID** field setup in the Supplier Stock Location relationship, as detailed in section 4.1.

## Invoice.AllowanceCharge

Element	Type	Use	Description
ChargeIndicator	IndicatorType	1	Set <b>true</b> if the AllowanceCharge is a charge, <b>false</b> if it is an allowance. For this release, only <b>true</b> (i.e. charges) is supported
AllowanceChargeReason	AllowanceChargeReasonType	1	The allowance/charge reason. Free-form text.
Amount	AmountType	1	The allowance/charge amount.
TaxCategory	TaxCategoryType	0..1	The tax category. Must be provided if TaxTotal is specified.
TaxTotal	TaxTotalType	0..1	The total tax for the allowance/charge. Defaults to <b>0.00</b> if not specified

### Example

```
<cac:AllowanceCharge>
  <cbc:ChargeIndicator>true</cbc:ChargeIndicator>
  <cbc:AllowanceChargeReason>Freight</cbc:AllowanceChargeReason>
  <cbc:Amount currencyID="AUD">10</cbc:Amount>
  + <cac:TaxCategory/>
  + <cac:TaxTotal/>
</cac:AllowanceCharge>
```

## Invoice.AllowanceCharge.TaxCategory

Element	Type	Use	Description
ID	IdentifierType	1	The <a href="#">tax category</a> identifier
Percent	PercentType	1	The tax rate, expressed as a percentage
TaxScheme	TaxSchemeType	1	The tax scheme

### Example

```
<cac:TaxCategory>
  <cbc:ID>S</cbc:ID>
  <cbc:Percent>10.00</cbc:Percent>
  + <cac:TaxScheme/>
</cac:TaxCategory>
```

## Invoice.AllowanceCharge.TaxCategory.TaxScheme

Element	Type	Use	Description
TaxTypeCode	CodeType	1	The <a href="#">tax type code</a>

### Example

```
<cac:TaxScheme>
  <cbc:TaxTypeCode>GST</cbc:TaxTypeCode>
</cac:TaxScheme>
```

## Invoice.AllowanceCharge.TaxTotal

Element	Type	Use	Description
TaxAmount	AmountType	1	The tax total
TaxAmount@currencyID	CurrencyCodeContentType	1	The <a href="#">currency code</a> that TaxAmount is expressed in

### Example

```
<cac:TaxTotal>
  <cbc:TaxAmount currencyID="AUD">1.00</cbc:TaxAmount>
</cac:TaxTotal>
```

## Invoice. TaxTotal

Element	Type	Use	Description
TaxAmount	AmountType	1	The tax total
TaxAmount@currencyID	CurrencyCodeContentType	1	The <a href="#">currency code</a> that TaxAmount is expressed in

### Example

```
<cac:TaxTotal>
  <cbc:TaxAmount currencyID="AUD">15.00</cbc:TaxAmount>
</cac:TaxTotal>
```

## Invoice. LegalMonetaryTotal

Element	Type	Use	Description
LineExtensionAmount	AmountType	1	The total of the line level LineExtensionAmounts
LineExtensionAmount@currencyID	CurrencyCodeContentType	1	The <a href="#">currency code</a> that LineExtensionAmount is expressed in
TaxExclusiveAmount	AmountType	1	The total amount, exclusive of taxes
TaxExclusiveAmount@currencyID	CurrencyCodeContentType	1	The <a href="#">currency code</a> that TaxExclusiveAmount is expressed in
ChargeTotalAmount	AmountType	0..1	The total charge amount
ChargeTotalAmount@currencyID	CurrencyCodeContentType	1	The <a href="#">currency code</a> that ChargeTotalAmount is expressed in
PayableAmount	AmountType	1	The payable amount
PayableAmount@currencyID	CurrencyCodeContentType	1	The <a href="#">currency code</a> that PayableAmount is expressed in

### Example

```
<cac:LegalMonetaryTotal>
  <cbc:LineExtensionAmount currencyID="AUD">140</cbc:LineExtensionAmount>
  <cbc:TaxExclusiveAmount currencyID="AUD">150</cbc:TaxExclusiveAmount>
  <cbc:ChargeTotalAmount currencyID="AUD">10</cbc:ChargeTotalAmount>
  <cbc:PayableAmount currencyID="AUD">165.00</cbc:PayableAmount>
</cac:LegalMonetaryTotal>
```

## Invoice. LegalMonetaryTotal.LineExtensionAmount

This is the total of the line level LineExtensionAmount amounts i.e.:

```
LineExtensionAmount =  $\sum$  LineExtensionAmount (at line level)
```

## Invoice. LegalMonetaryTotal.TaxExclusiveAmount

This is the total amount, exclusive of taxes i.e.

```
TaxExclusiveAmount =
Σ LineExtensionAmount (at line level) +
Σ Amount (from AllowanceCharge at document level where ChargeIndicator = "true") -
Σ Amount (from AllowanceCharge at document level where ChargeIndicator = "false")
```

### Invoice. LegalMonetaryTotal.ChargeTotalAmount

This is the total charge amount i.e.:

```
ChargeTotalAmount =
Σ Amount (from AllowanceCharge at document level where ChargeIndicator = "true")
```

### Invoice. LegalMonetaryTotal.PayableAmount

This is the total payable amount for the invoice i.e.:

```
PayableAmount = TaxExclusiveAmount (at document level) +
ΣTaxAmount (from TaxTotal at document level)
```

### Invoice. InvoiceLine

Element	Type	Use	Description
ID	IdentifierType	1	The seller assigned identifier for the invoice line
InvoicedQuantity	QuantityType	1	The quantity of items on the invoice line
InvoicedQuantity@unitCode	String	1	The <a href="#">unit of measure code</a> for the quantity
LineExtensionAmount	AmountType	1	The line total, excluding taxes
LineExtensionAmount@currencyID	CurrencyCodeContentType	1	The <a href="#">currency code</a> that LineExtensionAmount is expressed in
OrderLineReference	OrderLineReferenceType	0..1	A reference to the original order line
PricingReference	PricingReferenceType	0..1	Used to express the wholesale price
TaxTotal	TaxTotalType	0..1	The total tax for the invoice line
Item	ItemType	1	The item being invoiced
Price	PriceType	1	The item price

#### Example

```
<cac:InvoiceLine>
  <cbc:ID>1</cbc:ID>
  <cbc:InvoicedQuantity unitCode="BX">1</cbc:InvoicedQuantity>
  <cbc:LineExtensionAmount currencyID="AUD">100</cbc:LineExtensionAmount>
+ <cac:OrderLineReference/>
+ <cac:PricingReference/>
+ <cac:TaxTotal/>
+ <cac:Item/>
+ <cac:Price/>
</cac:InvoiceLine>
```

### Invoice.InvoiceLine.OrderLineReference

Element	Type	Use	Description
LineID	IdentifierType	1	The order line identifier
OrderReference	OrderReferenceType	0..1	The order reference

### Example

```
<cac:OrderLineReference>
  <cbc:LineID>12384</cbc:LineID>
</cac:OrderLineReference>
```

## Invoice.InvoiceLine.OrderLineReference.OrderReference

Element	Type	Use	Description
ID	IdentifierType	1	The order identifier

### Example

```
<cac:OrderReference>
  <cbc:ID>726</cbc:ID>
</cac:OrderReference>
```

### Notes

1. **OrderReference** only needs to be provided if an invoice is associated with multiple orders.

## Invoice.InvoiceLine.PricingReference

Element	Type	Use	Description
AlternativeConditionPrice	PriceType	1	The price expressed in terms other than the actual price, e.g., the list price vs. the contracted price, or the price in bags vs. the price in kilos, or the list price in bags vs. the contracted price in kilos

### Example

```
<cac:PricingReference>
  + <cac:AlternativeConditionPrice/>
</cac:PricingReference>
```

## Invoice.InvoiceLine.PricingReference.AlternativeConditionPrice

Element	Type	Use	Description
PriceAmount	AmountType	1	The wholesale price
PriceAmount@currencyID	CurrencyCodeContentType	1	The <a href="#">currency code</a> that PriceAmount is expressed in
PriceTypeCode	CodeType	1	The price type code. Must be <b>WH</b>

### Example

```
<cac:AlternativeConditionPrice>
  <cbc:PriceAmount currencyID="AUD">105</cbc:PriceAmount>
  <cbc:PriceTypeCode>WH</cbc:PriceTypeCode>
</cac:AlternativeConditionPrice>
```

## Invoice.InvoiceLine.TaxTotal

Element	Type	Use	Description
TaxAmount	AmountType	1	The invoice line tax amount
TaxAmount@currencyID	CurrencyCodeContentType	1	The <a href="#">currency code</a> that TaxAmount is expressed in
TaxSubtotal	TaxSubtotalType	1	The tax subtotal

### Example

```
<cac:TaxTotal>
  <cbc:TaxAmount currencyID="AUD">10.00</cbc:TaxAmount>
  + <cac:TaxSubtotal/>
</cac:TaxTotal>
```

### Invoice.InvoiceLine.TaxTotal.Taxsubtotal

Element	Type	Use	Description
TaxAmount	AmountType	1	The tax amount
TaxAmount@currencyID	CurrencyCodeContentType	1	The <a href="#">currency code</a> that TaxAmount is expressed in
TaxCategory	TaxCategoryType	1	The tax category

### Example

```
<cac:TaxSubtotal>
  <cbc:TaxAmount currencyID="AUD">10.00</cbc:TaxAmount>
  + <cac:TaxCategory/>
</cac:TaxSubtotal>
```

### Invoice.InvoiceLine.TaxTotal.Taxsubtotal.TaxCategory

Element	Type	Use	Description
ID	IdentifierType	1	The <a href="#">tax category identifier</a>
Percent	PercentType	1	The tax rate, as a percentage
TaxScheme	TaxSchemeType	1	The tax scheme

### Example

```
<cac:TaxCategory>
  <cbc:ID>S</cbc:ID>
  <cbc:Percent>10.00</cbc:Percent>
  + <cac:TaxScheme/>
</cac:TaxCategory>
```

### Invoice.InvoiceLine.TaxTotal.Taxsubtotal.TaxCategory.TaxScheme

Element	Type	Use	Description
TaxTypeCode	CodeType	1	The <a href="#">tax type code</a>

### Example

```
<cac:TaxScheme>
  <cbc:TaxTypeCode>GST</cbc:TaxTypeCode>
</cac:TaxScheme>
```

### Invoice.InvoiceLine.Item

Element	Type	Use	Description
Name	TextType	1	The item name
BuyerItemIdentification	ItemIdentificationType	0..1	The buyer assigned item identifier
SellerItemIdentification	ItemIdentificationType	0..1	The seller assigned item identifier

### Example

```
<cac:Item>
  <cbc:Name>product1 name</cbc:Name>
  + <cac:BuyersItemIdentification/>
  + <cac:SellersItemIdentification/>
</cac:Item>
```

### Notes

1. OpenVPMS requires that one or both of **BuyersItemIdentification** and **SellersItemIdentification** be provided.
2. If **BuyersItemIdentification** is used, it must correspond to the **BuyersItemIdentification** from the original **OrderLine**.
3. If **SellersItemIdentification** is used, it must correspond to the **Reorder Code** found in OpenVPMS product's supplier information for the supplier generating the invoice. **SellersItemIdentification** may be used if there is no **OrderLine** associated with an **InvoiceLine**.

### Invoice.InvoiceLine.Item.BuyersItemIdentification

Name	Type	Use	Description
ID	IdentifierType	1	The buyer assigned item identifier

### Example

```
<cac:BuyersItemIdentification>
  <cbc:ID>12091</cbc:ID>
</cac:BuyersItemIdentification>
```

### Invoice.InvoiceLine.Item.SellersItemIdentification

Name	Type	Use	Description
ID	IdentifierType	1	The seller assigned item identifier

### Example

```
<cac:SellersItemIdentification>
  <cbc:ID>product1</cbc:ID>
</cac:SellersItemIdentification>
```

### Invoice.InvoiceLine.Price

Name	Type	Use	Description
PriceAmount	AmountType	1	The price for the base quantity of the item, excluding any taxes.
PriceAmount@currencyID	CurrencyCodeContentType	1	The <a href="#">currency code</a> that PriceAmount is expressed in
BaseQuantity	QuantityType	0..1	The base quantity that the price applies to.
BaseQuantity@unitCode	String	1	The <a href="#">unit of measure code</a> for the quantity.

### Example

```
cac:InvoiceLine>
  <cbc:InvoicedQuantity unitCode="BO">10</cbc:InvoicedQuantity>
  <cbc:LineExtensionTotalAmount currencyID="AUD">240.00</cbc:LineExtensionTotalAmount>
  <cac:Item>
    <cbc:Name>Alamycin 10</cbc:Name>
    <cac: SellersItemIdentification>
      <cbc:ID>1024</cbc:ID>
    </cac: SellersItemIdentification>
  </cac:Item>
  <cac:Price>
    <cbc:PriceAmount currencyID="AUD">24.00</cbc:PriceAmount>
    <cbc:BaseQuantity unitCode="BO">1</cbc:BaseQuantity>
  </cac:Price>
</cac:InvoiceLine>
```

The example above shows that 10 bottles of Alamycin 10 have been invoiced at a total price of \$240, and that each bottle has a price of \$24.

The *PriceAmount* and the *BaseQuantity* describe the supplier's base unit for the product. Note that *PriceAmount* is always specified tax exclusive. For this release, only a *BaseQuantity* of 1 is supported.

## 6.4 DocumentReference

Element	Type	Use	Description
ID	IdentifierType	1	Identifies the document being referred to
IssueDate	IssueDateType	0..1	The date the document was issued
DocumentType	TextType	1	The document type e.g. <b>OrderResponseSimple, Invoice</b>

## 6.5 Document

Element	Type	Use	Description
Any	Any	1	The UBL document

### Example

```
<esci:Document>
  + <invoice:Invoice/>
</esci:Document>
```

## 7 Code Lists

### 7.1 Currency codes

Currency codes used in amounts must conform to the ISO 4217 standard. This specifies currencies as three letter codes e.g. **AUD** for “Australian Dollar”, **GBP** for “Pound Sterling”.

While UBL allows different currency codes to be expressed for different amounts in a document, this release of ESCI only supports a single currency per document.

UBL provides a code list to validate currency codes against, at <http://docs.oasis-open.org/ubl/cs-UBL-2.0/cl/gc/cefact/CurrencyCode-2.0.gc>

### 7.2 Unit of Measure codes

Unit of measure codes are used in quantities to specify the type of the quantity, e.g. **BX** for “box”, and **EA** for “each”. These must conform to the UN/ECE rec 20 standard.

UBL provides a code list to validate these against, at <http://docs.oasis-open.org/ubl/cs-UBL-2.0/cl/gc/cefact/UnitOfMeasureCode-2.0.gc>

### 7.3 Tax Category Identifiers

Tax category identifiers are used to specify the category of tax applied to an item, e.g. **S** for “Standard-Rated”, **Z** for “Zero-Rated”, **E** for “Exempt from tax”.

These must be specified according to UN/CEFACT Code List 5305 “Duty or Tax or Fee Category Code” version D09B. See

[http://www.unece.org/unecefact/codelist/standard/UNECE\\_DutyorTaxorFeeCategoryCode\\_D09B.xsd](http://www.unece.org/unecefact/codelist/standard/UNECE_DutyorTaxorFeeCategoryCode_D09B.xsd) for more details.

### 7.4 Tax Type Codes

Tax schemes specify the type of tax payable via a TaxTypeCode, e.g. **GST**, or **VAT**. These must be specified according to UN/CEFACT Code List 5153 “Duty Tax Fee Type Code” version D09B. See

[http://www.unece.org/unecefact/codelist/standard/UNECE\\_DutyTaxFeeTypeCode\\_D09B.xsd](http://www.unece.org/unecefact/codelist/standard/UNECE_DutyTaxFeeTypeCode_D09B.xsd) for more details.

### 7.5 Price Type Codes

Price type code identifiers are used to identify the type of a price. For ESCI, these are currently only relevant to the **InvoiceLine.PricingReference.AlternativeConditionPrice** element, to specify that the price is a wholesale price.

These must be specified according to UN/CEFACT Code List 5375 “Price Type Code” version D09B. See [http://www.unece.org/unecefact/codelist/standard/UNECE\\_PriceTypeCode\\_D09B.xsd](http://www.unece.org/unecefact/codelist/standard/UNECE_PriceTypeCode_D09B.xsd) for more details.

## 7.6 Country codes

There is currently no requirement to include country codes in addresses. If specified however, any country code must conform to the ISO 3166-1 “Country codes” standard. This expresses country codes using two characters e.g. **AU** for “Australia”, **NZ** for “New Zealand”.

UBL provides a code list to validate these against, at <http://docs.oasis-open.org/ubl/cs-UBL-2.0/cl/gc/default/CountryIdentificationCode-2.0.gc>

## 7.7 Country Sub-entity codes

There is currently no requirement to include country sub-entity codes (e.g. states, territories or provinces) in addresses. If specified however, any code must conform to the ISO 3166-2 “Country subdivision code” standard.

See [http://www.iso.org/iso/country\\_codes/background\\_on\\_iso\\_3166/iso\\_3166-2.htm](http://www.iso.org/iso/country_codes/background_on_iso_3166/iso_3166-2.htm) for the source of the standard. ISO charges a fee for the code list – see [http://en.wikipedia.org/wiki/ISO\\_3166-2](http://en.wikipedia.org/wiki/ISO_3166-2) for a synopsis and references to older versions.

## **8 Future Development**

Areas for future development include:

- Order cancellation
- Order amendment
- Catalogues
- Different calculation models